



Tradition and Innovation


# Cold-fill Nebuliser | Atomiser



## Recommended for disinfecting, pest control, fumigation

This is a compact device with integrated 4ℓ tank which is easy to transport and operate. It is equipped with a padded, adjustable harness to provide increased comfort and autonomy. It comes with an exclusive "dispersion head" (ULV/LV) for spatial and residual applications and a instant flow cut-off valve to avoid waste and environmental contamination.

### Ideal for:



Pest Control  
Fumigation



Residential use  
Difficult to reach places  
Hospitals



Public Spaces  
Squares Parks



Poultry farms  
Greenhouses  
Gardens

**NEW** **ELECTRIC MOTOR**



+ power

+ strength

+ efficiency



Codes: 0445.70 (127V) | 0445.80 (220V)



# Compact, easy to handle and transport



- 1** Precision flow regulator valve offering a wide flow range;
- 2** Detachable 4-meter power cord and fusible (15A/127V and 10A/220V), for motor protection;
- 3** Trigger with instant liquid cut-off to avoid waste and environmental contamination;
- 4** Dispersion head (UBV / BV) with sturdy plastic cover;
- 5** Powerful motor for ULV and LV operation and for spatial or residual application;
- 6** Translucent tank and filtered drain for easier cleaning;
- 7** Motor with independent cooling system and filter element to increase durability.

## SPECIAL FEATURES

**The Electric Cold Spray Nebuliser can apply two droplet sizes:** larger droplets, when the on-off switch is in position "1", or smaller droplets in position "2"

**Ideal for applying:** Disinfectants, insecticides, fungicides, dust mite sprays, mould sprays, germicides, deodorants etc.

**On site application including:** Disinfecting workplaces against airborne viruses e.g. clinics, gyms, treatment rooms, hospitals, waiting rooms. Fogging flower (Rose) storage areas, flower shops, greenhouses, schools, hotels, food production facilities, silos and public spaces. Excellent for airborne vaccine application at poultry sheds, poultry barns, pig pens and kennels.



## TECHNICAL SPECIFICATIONS

|                                 |                    |                                    |   |
|---------------------------------|--------------------|------------------------------------|---|
| Electric motor power .....      | 1.400w             | Max. Vertical reach* .....         | 8m (26,2ft)                               |
| Voltage .....                   | 127v ou 220v       | Droplet size - DMV (microns) ..... | 29 e 63 µm                                |
| Motor speed                     |                    | Max. flowrate* .....               | 400ml/min                                 |
| 1 (minimum) / 2 (maximum) ..... | 17.200 - 21.100rpm | Min. flowrate* .....               | 15ml/min                                  |
| Tank operating capacity .....   | 4l (1,06gal)       | Dry weight .....                   | 5,2kg                                     |
| Max. Horizontal reach* .....    | 11m (36,1ft)       | Carton size .....                  | 525 x 230 x 65mm<br>(20,7 x 9,1 x 14,4in) |

\* Approximate figures obtained using clean water, however results may vary depending on the product used, application method, weather conditions, altitude and voltage variations.

**Guarany's Mission:** our mission is to develop high quality, products of high technology, while respecting the environment, people and markets and ensuring satisfaction at all times for both customers and employees.

### DISTRIBUTER

**Export Department**  
 +55 (11) 2118-8400  
 export@guaranyind.com.br  
[www.guaranyind.com.br](http://www.guaranyind.com.br)



**Guarany**  
 Tradition and Innovation

**PSP** | THE PROFESSIONAL SPRAYERS  
 PEOPLE

[www.prosprayers.co.uk](http://www.prosprayers.co.uk)  
 tel: 01273400092  
 e-mail: info@prosprayers.co.uk