



SpotOn®

SPRAYER CALIBRATOR MODEL SC-2

US Patent # 8297131

ACCURATE FLOW RATE, APPLICATION RATE, AND TIP WEAR MEASUREMENT IN SECONDS



NEW!

- Automatically calculates tip wear in % and application rate in GPA/LPH
- Increased capacity and accuracy over previous model

SPECIFICATIONS

Range:	0.02 – 2.25 GPM, 0.08 – 8.52 LPM, 3 – 288 oz/min (GPM in US Gallons)
Accuracy:	+/- 2% or 1 Digit
Resolution:	0.01 GPM, 0.01 L/min, 1 oz/min
Fluid Compatibility:	Water & Water Based Solutions Only
Battery:	CR2032 Included (3 Year Battery Life)
Size:	3" (7.6 cm) Dia x 8.75" (22 cm) Tall
Weight:	0.6 lbs (272 g)

Every unit is hand calibrated and verified with water to assure top accuracy in the field.



FEATURES

- No calculations or app download required:
Automatically calculates and displays tip flow rate in GPM, LPM, oz/min, tip wear in %, and application rate in GPA/LPH (just enter your speed and nozzle spacing).
- Fast and simple operation:
Readings in about 10 seconds per tip.
- Quickly find worn spray nozzle tips:
Industry guidelines recommend tip replacement once flow rate exceeds that of the new tip by 10%.
- Accurately measure true tip flow rate:
Today's high-tech sprayers can only be properly calibrated and confirmed with this knowledge.

Visit us at www.innoquestinc.com for complete details.

YOUTUBE.COM



SEE THE DEMO VIDEO, SEARCH SpotOn Sprayer Calibrator Model SC-2

Sprayer Calibrator Model SC-2 • Item #38790 • One year warranty • Made in USA